



Product Introduction

Mixer Mill DH-S2010 instrument, which is a product launched for "small samples". Mixer Mill can quickly and effectively dry or wet grind hard, soft, and elastic samples within 1-3 minutes. It can also achieve the purpose of mixing and homogenizing powder and turbid liquids. It can be used for cryogenic grinding with liquid nitrogen, as well as for biological cell disruption and DNA/RNA extraction.

The types of samples that the high-throughput tissue grinder can grind include: plant tissues, animal tissues, cells, bacteria, spores, and yeasts.



Product Applications

- 1. Within 1-3 minutes, 24, 48, and 192 samples can be quickly and effectively ground.
- 1. Within 1-3 minutes, 24, 48, and 192 samples can be quickly and effectively ground.
- the LAWSON grinding kit in liquid nitrogen, and quickly fix the grinding tank to start grinding after it is fully frozen.
- 3. Various centrifuge tubes, PCR tube adapters, or grinding jars of different materials can be selected.
- 4. 8-shaped vibration, sample grinding without dead corners.
- 5. Simple and safe operation design.
- 6. Exquisite and compact appearance.
- 7. Screw cap grinding jar, sealed and dustproof.
- 8. Screw cap grinding jar, sealed and dustproof.
- 9. Suitable for dry and wet grinding of a variety of samples.
- 10. Separate design, use closed net letter special grinding tank or disposable centrifuge tube to avoid sample cross contamination.
- 11. 3 different grinding modes (dry, wet or cryogenic).
- 12. 20 SOPs can be stored.
- the movement of the balls result in the intensive mixing of the sample.

Function Principle

The grinding jars of the DH-S2010 perform radial oscillations in a horizontal position. The inertia of the grinding balls causes them to impact with high energy on the sample material at the rounded ends of the grinding jars and pulverize it. Also, the movement of the grinding jars combined with the movement of the balls result in the intensive mixing of the sample. The degree of mixing can be increased even further by using several smaller balls. If several small balls are used (e.g. glass beads) then, for example, biological cells can be disrupted. The large frictional impact effects between the beads ensure effective cell disruption.

• 2. By pre-freezing the sample and the grinding tank, you can successfully grind the heat-sensitive and elastic materials, immerse the sample and

• 13. Grinding jars of the DH-S2010 perform radial oscillations in a horizontal position. The inertia of the grinding balls causes them to impact with high energy on the sample material at the rounded ends of the grinding jars and pulverize it. Also, the movement of the grinding jars combined with



Model	DH-S2010
Applications	size reduction, mixing, homogenization, cell disruption, cryo
Field of application	agriculture, biology, chemistry / plastics, construction mater
	ment / recycling, food, geology / metallurgy, glass / ceramics
Feed material	hard, medium-hard, soft, brittle, elastic, fibrous
Size reduction principle	impact, friction
Material feed size	≤8 mm
Final fineness	~ 5 µm
Batch size / feed quantity	max. 2 x 50 ml
No. of grinding stations	2
Setting of vibrational frequency	digital, 0 – 70 Hz (0 – 3000 min-1)
Typical mean grinding time	30 s – 2 min
Grinding method	Dry grinding/Wet grinding/Cryogenic grinding
Cell disruption with reaction vials	yes, up to 96 x 2.0 ml

nogenization, cell disruption, cryogenic grinding

stry / plastics, construction materials, engineering / electronics, environ-

logy / metallurgy, glass / ceramics, medicine / pharmaceuticals

Technical Parameters

Self-centering clamping device	yes
Type of grinding jars	screw top design
Material of grinding tools	hardened steel, stainless s
Grinding ball material	Alloy steel, chrome steel, z
Grinding jar sizes	1.5 ml / 5 ml / 10 ml / 25 m
Setting of grinding time	digital, 10 s – 99 min
Storable SOPs	20
Power consumption	150 W
W x H x D closed	380*270*490
Net weight	26kg
Electrical supply data	100-240 V, 50/60 Hz

s steel, tungsten carbide, agate, zirconium oxide, PTFE

el, zirconia, tungsten carbide, quartz sand

ml / 35 ml / 50ml